

What is claimed is:

1. An air quality management apparatus, for use in an electrostatographic printer for making color images on receiver members, which printer has a paper conditioning station associated therewith and which printer includes a first interior volume and a second interior volume, which first interior volume includes a fusing station for fusing said color images on said receiver members, which second interior volume includes a number of tandemly arranged electrostatographic image-forming modules, said second interior volume also including charging devices, image writers, toning stations and cleaning stations operating in conjunction with said electrostatographic image-forming modules, said second interior volume differentiated from said first interior volume by at least one separating member, said air quality management apparatus comprising:
  - an open-loop portion for managing of an air quality of air flowing through and included in said first interior volume, which first interior volume is provided with at least one inlet port and at least one outlet port, said first interior volume including a plurality of throughput pathways connecting said at least one inlet port with said at least one outlet port, said open-loop portion including at least one air moving device for drawing ambient air from outside of said printer through said at least one inlet port to said first interior volume and moving said air included in said first interior volume towards and through said at least one outlet port for expulsion as expelled air, said at least one air moving device providing a specified total airflow rate between said at least one inlet port and said at least one outlet port;
  - a recirculation portion for managing of an air quality of air included in and circulating within said second interior volume, said recirculation portion including an air-conditioning device having an entrance and at least one exit, each of said at least one exit providing a respective post-exit airflow included in at least one post-exit airflow, which air-conditioning device provides conditioning of said air included in said second interior volume, said recirculation portion of said air quality management apparatus further including at least one air recirculation

device, said at least one air recirculation device for moving said air included in said second interior volume at a specified total rate of recirculation through said air-conditioning device, such that air-conditioned air leaving said at least one exit of said air-conditioning device is urged by said at least one air recirculation device through a plurality of recirculation pathways included in said second interior volume, said plurality of pathways included in said second interior volume being conjoined into a common duct for carrying air for recycling to a filtering unit, said filtering unit located within said common duct, said filtering unit for removing contaminants from said air for recycling in said air-conditioning device;

wherein, excepting said at least one inlet port to said first interior volume and said at least one outlet port from said first interior volume, said first interior volume and said second interior volume are substantially sealed from said ambient air outside of said printer;

wherein said expelled air carries out, from said first interior volume, excess heat and aerial contamination generated within said first interior volume;

wherein said recirculation portion of said air quality management apparatus includes at least one mechanism for removing, during said recycling, aerial contaminants from said air included within said second interior volume;

wherein said conditioning and recycling by said air-conditioning device includes a temperature controller for temperature control, within a predetermined temperature range, of said at least one post-exit airflow from said air-conditioning device; and

wherein said conditioning and recycling by said air-conditioning device includes a relative humidity controller for relative humidity control, within a predetermined relative humidity range, of said at least one post-exit airflow from said air-conditioning device.

2. The air quality management apparatus according to Claim 1, wherein said at least one separating member defines at least one leakage pathway between said first interior volume and said second interior volume, said at least one leakage pathway associated with a leakage flow rate of air from said first interior volume to said second interior volume and a substantially equal

leakage flow rate of air from said second interior volume to said first interior volume, which leakage flow rate from said second interior volume to said first interior volume is a predetermined fraction of said specified total rate of recirculation within said recirculation portion of said air quality management apparatus.

3. The air quality management apparatus according to Claim 2, wherein said predetermined fraction is less than about 0.33.

4. The air quality management apparatus according to Claim 3, wherein said predetermined fraction includes substantially zero.

5. The air quality management apparatus according to Claim 2, wherein said at least one separating member comprises a transport web for transporting said receiver members past said number of tandemly arranged electrostatographic image-forming modules.

6. The air quality management apparatus according to Claim 5, wherein said transport web has a form of a tube encircling a third interior volume, said third interior volume communicating with said at least one leakage pathway, said communicating thereby resulting in a formation within said third interior volume of a mixed air, said mixed air having characteristics intermediate between characteristics of said air included in said first interior volume and characteristics of said air included in said second interior volume, said characteristics including temperature and relative humidity.

7. The air quality management apparatus according to Claim 1, wherein said aerial contamination carried out from said first interior volume by said expelled air includes at least one of a group of contaminants, said group of contaminants comprising: amines, acrolein, ozone, fuser oil vapor, water vapor, and particulates.

8. The air quality management apparatus according to Claim 1, wherein a device is provided for purpose of directing, at a specified input rate, a

refreshing flow of filtered air from outside said printer into said second interior volume through at least one input pipe, with a compensating airflow rate of approximately equal magnitude to said specified input rate leaving said second interior volume to at least one location outside said second interior volume.

5                    9.        The air quality management apparatus according to Claim 8, wherein said specified input rate divided by said total recirculation rate is less than about 0.2.

10                   10.       The air quality management apparatus according to Claim 9, wherein said specified input rate divided by said total recirculation rate is less than about 0.05.

15                   11.       The air quality management apparatus according to Claim 1, wherein in associative proximity to each said at least one inlet port is provided an amine filter, which amine filter is for a purpose of removing amine contaminants from said ambient air entering said first interior volume through said at least one inlet port.

12.       The air quality management apparatus according to Claim 1, wherein in associative proximity to each said at least one inlet port is provided a particulate filter for a purpose of removing particulate contaminants from said ambient air entering said first interior volume through said at least one inlet port.

20                   13.       The air quality management apparatus according to Claim 1, wherein said recirculation portion includes at least one device for removing ozone from said air included in said second interior volume.

25                   14.       The air quality management apparatus according to Claim 1, wherein said recirculation portion includes at least one coarse particulate filter for removing coarse particles from said air included in said second interior volume, said at least one coarse particulate filter included in said filtering unit.

15. The air quality management apparatus according to Claim 1, wherein said recirculation portion includes at least one fine particulate filter for removing fine particles from said air included in said second interior volume, said at least one fine particulate filter included in said filtering unit.

5 16. The air quality management apparatus according to Claim 1, wherein said expelled air is led through a duct connecting said at least one outlet port to an external mechanism for air disposal.

10 17. The air quality management apparatus according to Claim 1, wherein said number of tandemly arranged electrostatographic image-forming modules is five and said specified total airflow rate through said first interior volume is approximately 1180 cubic feet per minute  $\pm$ 200 cubic feet per minute.

15 18. The air quality management apparatus according to Claim 1, wherein said number of tandemly arranged electrostatographic image-forming modules is five and said specified total rate of recirculation of said air included in said second interior volume is approximately 1180 cubic feet per minute, which specified total rate of recirculation is included in a range between approximately 1080 cubic feet per minute and 1380 cubic feet per minute.

20 19. The air quality management apparatus according to Claim 1, wherein air recirculated to said air-conditioning device for said conditioning has had coarse and fine particulates removed therefrom by said filtering unit, which air is divided into a first stream and a second stream, said first stream cooled by flowing past cooling fins for cooling said first stream, said cooling fins in thermal contact with an evaporator coil, said evaporator coil in the form of a thermally conductive tube containing a refrigerant being passed in the form of a cold  
25 gas/liquid mixture through the interior of said tube, said cooling fins being thermally conductive and thereby cooled by said evaporator coil in thermal contact with said cold gas/liquid mixture, whereinafter having moved past said evaporator coil, said first stream is mixed with said second stream to form a recombined stream, which recombined stream is flowed in a primary duct through

an internal filtering unit, which internal filtering unit includes in order of flow-through an ozone filter and an amine filter, which combined stream after being filtered of ozone and amines passes by thermally conductive heating fins for heating said recombined stream, said thermally conductive heating fins being in thermal contact with a reheat coil, said reheat coil for intermittent use for intermittently heating said recombined stream, wherein during said intermittent use a flow of said refrigerant in the form of a hot compressed gas is passed through said reheat coil, said reheat coil being a thermally conductive tube containing said refrigerant, said intermittent use for intermittently heating said recombined stream controlled by said temperature controller.

20. The air quality management apparatus according to Claim 19, wherein in said air-conditioning device said recombined stream, after passing said reheat coil, is flowed through a humidification unit for intermittently humidifying said recombined stream and from thence through a main recirculation device, whereinafter said recombined stream is sensed by a temperature sensor for sensing a temperature of said recombined stream and by a relative humidity sensor for sensing a relative humidity of said recombined stream, said temperature sensor connected to said temperature controller and said relative humidity sensor connected to said relative humidity controller, said recombined stream thereafter divided as necessary for flowing through said at least one exit from said air-conditioning device.

21. The air quality management apparatus according to Claim 20, wherein said temperature of said recombined stream sensed by said temperature sensor is kept within a predetermined temperature range having a lowest temperature and a highest temperature, said intermittent use for intermittently heating said recombined stream comprising an activation by a turn-on signal from said temperature controller when said temperature of said recombined stream as sensed by said temperature sensor is lower than a target temperature, said intermittent use for intermittently heating said recombined stream further comprising a deactivation by a turn-off signal from said

temperature controller when said temperature of said recombined stream being sensed by said temperature sensor is higher than said target temperature, which target temperature is approximately midway between said lowest temperature and said highest temperature.

5                    22.     The air quality management apparatus according to Claim 21, wherein said turn-on signal activates a solenoid valve, which solenoid valve thereby opens a gate for flowing said refrigerant in the form of said hot compressed gas through said reheat coil, and wherein said turn-off signal activates said solenoid valve to close said gate, thereby stopping said flowing of said  
10 refrigerant through said reheat coil.

                    23.     The air quality management apparatus according to Claim 22, wherein said lowest temperature is approximately 20.0°C and said highest temperature is approximately 22.2°C.

                    24.     The air quality management apparatus according to Claim  
15 20, wherein said relative humidity of said recombined stream sensed by said relative humidity sensor is maintained within a predetermined relative humidity range by an intermittent use of said humidification unit, said predetermined relative humidity range having a lowest relative humidity and a highest relative humidity, said intermittent use of said humidification unit comprising an  
20 activation by a turn-on signal from said relative humidity controller when said relative humidity of said recombined stream as sensed by said relative humidity sensor is lower than a target relative humidity, said intermittent use of said humidification unit further comprising a deactivation by a turn-off signal from said relative humidity controller when said relative humidity of said recombined  
25 stream being sensed by said relative humidity sensor is higher than said target relative humidity, which target relative humidity is approximately midway between said lowest relative humidity and said highest relative humidity.

25. The air quality management apparatus according to Claim 24, wherein said lowest relative humidity is approximately 30 percent and said highest relative humidity is approximately 40 percent.

26. The air quality management apparatus according to Claim 5 20, said humidification unit comprising a drip mechanism and a wettable pad for use with said drip mechanism, wherein said activation causes said drip mechanism to drip water on to said wettable pad so as to maintain thereby a wetness of said wettable pad, said recombined stream being humidified during said activation by flowing past and contacting said wetness, said deactivation preventing said water 10 from being dripped on to said wettable pad and said wetness not maintained.

27. The air quality management apparatus according to Claim 26, said humidification unit further comprising a collection mechanism for collecting excess water dripping from said wettable pad and a pumping mechanism for recycling said excess water for return to said drip mechanism.

28. The air quality management apparatus according to Claim 15 19, said recombined stream flowed from a continuation of said primary duct into at least one secondary duct, each said at least one secondary duct carrying a respective subflow of said recombined stream, said respective subflow flowing through a respective humidification unit for intermittent use for intermittently 20 humidifying said respective subflow, said respective subflow sensed after passing said respective humidification unit by a respective temperature sensor and by a respective relative humidity sensor, said respective temperature sensor connected to said temperature controller and said respective relative humidity sensor connected to said relative humidity controller, said respective subflow moving 25 toward a respective exit included in said at least one exit from said air-conditioning device, from which respective exit is flowed a respective post-exit subflow, said respective post-exit subflow providing a respective individually air-conditioned air,



wherein said temperature of said respective post-exit subflow is continuously sensed as a respective temperature signal by said respective temperature sensor, each said respective temperature signal being utilized at any instant in said temperature controller by an algorithm to calculate a control temperature, said control temperature calculated according to said algorithm being dependent on each said respective temperature signal, said control temperature maintained within a predetermined temperature range bounded by a lowest temperature and a highest temperature, said intermittent use for intermittently heating said recombined stream comprising an activation by a turn-on signal from said temperature controller when said control temperature is lower than a target control temperature, said intermittent use for intermittently heating said recombined stream further comprising a deactivation by a turn-off signal from said temperature controller when said control temperature is higher than said target control temperature, which target temperature is approximately midway between said lowest temperature and said highest temperature; and

wherein said relative humidity of said respective post-exit subflow is continuously sensed as a respective relative humidity signal by said respective relative humidity sensor, said intermittent use for intermittently humidifying said respective subflow according to signals sent to said respective humidification unit from said humidity controller, said relative humidity controller being preset so as to maintain for each respective post-exit subflow a respective relative humidity, which respective relative humidity lies within a respective predetermined relative humidity range for said respective post-exit subflow, said respective predetermined relative humidity range bounded by a respective lowest relative humidity and a respective highest relative humidity, wherein in response to a respective turn-on signal from said humidity controller, a respective activation of said respective humidification unit by said relative humidity controller starts a respective active humidification of said respective subflow when said respective relative humidity is lower than a respective target relative humidity, and in response to a respective turn-off signal from said humidity controller, a respective deactivation of said respective humidification unit by said relative humidity

controller stops said active humidification when said respective relative humidity is higher than said respective target relative humidity, said respective target relative humidity being approximately midway between said respective lowest relative humidity and said respective highest relative humidity.

5                   29.     The air quality management apparatus according to Claim 19,

                  wherein said recombined stream is flowed past an auxiliary post-reheat temperature sensor and then through a continuation of said primary duct into at least one secondary duct, each said at least one secondary duct carrying a  
10   respective subflow of said recombined stream, said respective subflow flowing past a respective temperature adjusting mechanism and through a respective humidification unit, said respective temperature adjusting mechanism and respective humidification unit arranged in a given order, said respective temperature adjusting mechanism for intermittent usage for adjusting a  
15   temperature of said respective subflow, said respective humidification unit for intermittent use for intermittently humidifying said respective subflow, said respective subflow sensed, after passing said respective temperature adjusting mechanism and said respective humidification unit, by a respective temperature sensor and by a respective relative humidity sensor, said respective temperature  
20   sensor connected to said temperature controller and said respective relative humidity sensor connected to said relative humidity controller, said respective subflow moving toward a respective exit included in said at least one exit from said air-conditioning device, from which respective exit is flowed a respective post-exit subflow, which respective post-exit subflow has a respective individual  
25   temperature and a respective individual relative humidity;

                  wherein said relative humidity of said respective post-exit subflow is continuously sensed as a respective relative humidity signal by said respective relative humidity sensor, said intermittent use for intermittently humidifying said respective subflow according to signals sent to said respective humidification unit  
30   from said humidity controller, said relative humidity controller being preset so as to maintain for each respective post-exit subflow a respective relative humidity,

which respective relative humidity lies within a respective predetermined relative humidity range for said respective post-exit subflow, said respective predetermined relative humidity range bounded by a respective lowest relative humidity and a respective highest relative humidity, wherein in response to a  
5 respective turn-on signal from said humidity controller, a respective activation of said respective humidification unit by said relative humidity controller starts a respective active humidification of said respective subflow when said respective relative humidity is lower than a respective target relative humidity, and in response to a respective turn-off signal from said humidity controller, a respective  
10 deactivation of said respective humidification unit by said relative humidity controller stops said active humidification when said respective relative humidity is higher than said respective target relative humidity, said respective target relative humidity being approximately midway between said respective lowest relative humidity and said respective highest relative humidity; and

15 wherein said temperature of said recombined stream sensed by said auxiliary post-reheat temperature sensor is kept within a predetermined post-reheat temperature range bounded by a least post-reheat temperature and an uppermost post-reheat temperature, said intermittent use for intermittently heating said recombined stream activated by a turn-on signal from said temperature controller  
20 when said temperature of said recombined stream sensed by said auxiliary post-reheat temperature sensor is lower than a target post-reheat temperature, said intermittent use for intermittently heating said recombined stream deactivated by a turn-off signal from said temperature controller when said temperature of said recombined stream sensed by said auxiliary post-reheat temperature sensor is  
25 higher than said target post-reheat temperature, which target post-reheat temperature is approximately midway between said least post-reheat temperature and said uppermost post-reheat temperature, and, wherein said intermittent usage for adjusting a temperature of said respective subflow is controlled according to respective signals sent to each said respective temperature adjusting mechanism  
30 from said temperature controller, said temperature controller being preset so as to maintain for each respective post-exit subflow a respective post-exit subflow

temperature, which respective post-exit subflow temperature lies within a respective predetermined temperature range for said respective post-exit airflow, said respective predetermined temperature range for said respective post-exit airflow bounded by a respective lowest temperature and a respective highest temperature, wherein in response to a respective activation signal from said temperature controller, a respective activation of said respective temperature adjusting mechanism by said temperature controller produces a respective alteration of said respective post-exit subflow temperature, and in response to a respective deactivation signal from said temperature controller, a respective deactivation of said respective temperature adjusting mechanism by said relative temperature controller causes said respective alteration of said respective subflow temperature to cease, said respective activation of said respective temperature adjusting mechanism by said respective activation signal taking place when said respective temperature sensor senses a respective post-exit subflow temperature that differs from a respective target post-exit subflow temperature for said respective post-exit subflow, said respective activation ceased by said deactivation signal when said respective post-exit subflow temperature is approximately equal to said respective target post-exit subflow temperature, which respective target post-exit subflow temperature is approximately midway between said respective lowest temperature and said respective highest temperature.

30. The air quality management apparatus according to Claim 29, wherein said turn-on signal activates a solenoid valve, which solenoid valve thereby opens a gate for flowing said refrigerant in the form of said hot compressed gas through said reheat coil, and wherein said turn-off signal activates said solenoid valve to close said gate, thereby stopping said flowing of said refrigerant through said reheat coil.

31. The air quality management apparatus according to Claim 19, said first stream having an airflow rate  $V_1$  and said second stream having an airflow rate  $V_2$ , wherein a ratio equal to  $V_1$  divided by  $V_2$  is a fixed ratio during operation of said air quality management apparatus.

32. The air quality management apparatus according to Claim 31, wherein said fixed ratio is approximately  $0.77 \pm 0.20$ .

33. The air quality management apparatus according to Claim 19, said first stream having an airflow rate  $V_1$  and said second stream having an  
5 airflow rate  $V_2$ , wherein a ratio equal to  $V_1$  divided by  $V_2$  is a controllably adjustable ratio during operation of said air quality management apparatus.

34. The air quality management apparatus according to Claim 1, wherein certain ones of said at least one post-exit airflow are provided with  
10 respective pipes, each of which respective pipes for delivering from said air-conditioning device a respective individually air-conditioned post-exit airflow to a respective toning station, thereby individually controlling a respective local temperature and a respective local relative humidity in the vicinity of said  
respective toning station.

35. The air quality management apparatus according to Claim  
15 1, wherein said at least one post-exit airflow provides module-ventilating air-conditioned air transported via ductage to a module-supplying input manifold provided with output pipes, through which said output pipes said module-ventilating air-conditioned air is delivered in approximately equal module-ventilating flows for respectively bathing each of said number of tandemly  
20 arranged electrostatographic image-forming modules, and wherein a respective exhaust pipe leads a respective module-exhausting outflow away from each of said image-forming modules to a module-exhausting output manifold, and from said module-exhausting output manifold for recirculation to said air-conditioning device.

36. The air quality management apparatus according to Claim  
25 1, wherein said at least one post-exit airflow provides subsystem-ventilating air-conditioned air transported via ductage to a subsystem-supplying input manifold, from which subsystem-supplying input manifold said subsystem-ventilating air-conditioned air is respectively piped in approximately equal subsystem flows to

each of said number of tandemly arranged electrostatographic image-forming modules, a respective subsystem flow divided into a respective charger-related portion of flow and a respective image-writer-related portion of flow, said respective charger-related portion of flow for ventilating at least one charging  
5 device in a respective image-forming module, and said respective image-writer-related portion of flow for cooling a respective image writer located in said respective image-forming module.

37. The air quality management apparatus according to Claim 1, wherein in a respective module a toning-station-related airflow is moved by  
10 said at least one air recirculation device into a developer-dust-removal duct included in said respective module, said developer-dust-removal duct being in associative proximity to a respective toning station included in said toning stations, said toning station generating a developer dust, which developer dust is entrained within said toning-station-related airflow for movement for movement  
15 via ducted passage to a particulate-related output manifold, and from said particulate-related output manifold for further movement by said at least one air recirculation device through an auxiliary developer dust filter, and from thence for recirculation to said air-conditioning device, said at least one air recirculation device including an auxiliary suction device for augmenting said further  
20 movement.

38. The air quality management apparatus according to Claim 1, wherein in a respective module a cleaning-station-related airflow is moved by  
said at least one air recirculation device into a cleaning-station-debris-removal duct included in said respective module, said cleaning-station-debris-removal duct  
25 being in associative proximity to a cleaning station included in said cleaning stations, said cleaning station generating a cleaning station debris, which cleaning station debris is entrained within said cleaning-station-related airflow for movement via ducted passage to a particulate-related output manifold, and from said particulate-related output manifold for further movement by said at least one  
30 air recirculation device through an auxiliary cleaning station debris filter, and from

thence for recirculation to said air-conditioning device, said at least one air recirculation device including an auxiliary suction device for augmenting said further movement.

39. The air quality management apparatus according to Claim 1, wherein associated with a respective module included in said number of tandemly arranged electrostatographic image-forming modules is an adjoining respective auxiliary chamber, said auxiliary chamber included in a plurality of auxiliary chambers in one-to-one relationship with said modules, said respective auxiliary chamber containing heat generating devices for operating said respective module, and which heat generating devices include: drive motors for rotating rotatable members included in said respective modules, power supplies, and circuit boards.

40. The air quality management apparatus according to Claim 39, wherein said at least one post-exit airflow provides auxiliary-chamber-ventilating air transported via ductage to an input manifold for ventilation of said plurality of auxiliary chambers, said input manifold for ventilation for delivering approximately equal auxiliary-chamber-input airflows to each auxiliary chamber of said plurality of auxiliary chambers, said input manifold for ventilation providing a piping connection to each said auxiliary chamber for transporting said auxiliary-chamber-ventilating air to said plurality of auxiliary chambers, and wherein an exhaust pipe from each said auxiliary chamber carries an auxiliary-chamber-exhausting airflow away from each said auxiliary chamber to an auxiliary-chamber-exhausting output manifold, and thence from said auxiliary-chamber-exhausting output manifold to said filtering unit.

41. The air quality management apparatus according to Claim 1, wherein said at least one air moving device included in said open-loop portion is chosen from a group including blowers, fans, and air suction mechanisms.

42. The air quality management apparatus according to Claim 1, wherein said at least one air recirculation device included in said recirculation

portion is chosen from a group including blowers, fans, and air suction mechanisms.

43. The air quality management apparatus according to Claim 1, wherein said specified total airflow rate of air managed in said open-loop  
5 portion and said specified total rate of recirculation of air managed in said recirculation portion differ by less than 5 percent from one another.

44. The air quality management apparatus according to Claim 1, wherein both the specified total airflow rate and the specified total rate of recirculation are reduced to stand-by values wherein said electrostatographic  
10 printer is in stand-by mode, so as to maintain said temperature control within said predetermined temperature range and to maintain said relative humidity control within said predetermined relative humidity range during stand-by mode.

45. The air quality management apparatus according to Claim 1, wherein at least one airflow rate of air included in said first interior volume and  
15 flowing through said plurality of throughput pathways is individually adjustable during operation of said electrostatographic printer.

46. The air quality management apparatus according to Claim 1, wherein at least one airflow rate of said air-conditioned air flowing through said plurality of recirculation pathways is individually adjustable during operation of  
20 said electrostatographic printer.

47. The air quality management apparatus according to Claim 1, wherein a percentage of one of said at least one post-exit airflow is divided into individual flows, each of said individual flows respectively flowing for delivery directly to certain ones of said charging devices for purpose of ventilating said  
25 certain ones of said charging devices, said individual flows subsequently flowing back for recirculation by said air-conditioning device.

48. The air quality management apparatus according to Claim 1, wherein said filtering unit includes a plurality of filters, said filters arranged in a



predetermined order for a sequential passage through said filters of said air for recycling, said plurality of filters including at least one of the following filters listed in said predetermined order: a coarse particulate filter, a fine particulate filter, an ozone filter, and an amine filter.

5                   49.     The air quality management apparatus according to Claim 1, said paper conditioning station included in said first interior volume, and wherein said plurality of pathways connecting said at least one inlet port with said at least one outlet port in said open-loop portion includes the following pathways:

10                   a pathway through a post fuser cooler, associated with said fusing station, for cooling said color images on said receiver members after fusing said color images on said receiver members in said fusing station, said pathway through a post fuser cooler including a cooling auxiliary fan;

15                   a pathway through a paper cooler, said pathway through a paper cooler including a pre-cooling auxiliary fan and a post-cooling auxiliary fan, said paper cooler included in said paper conditioning station included in said first interior volume;

                  a pathway through a paper heater, said paper heater included in said paper conditioning station included in said first interior volume; and

20                   one or more pathways through frame portions of said printer, said frame portions included in said first interior volume.

25                   50.     The air quality management apparatus according to Claim 49, wherein said managing of an air quality of air flowing through and included in said first interior volume includes removal of heat, generated within said first interior volume, by said air flowing through and included in said first interior volume.

                  51.     The air quality management apparatus according to Claim 50, wherein said heat generated within said first interior volume is generated according to the following heat generation rates: at least about 1000 watts from said post fuser cooler, at least about 300 watts from said cooling auxiliary fan, at

least about 1000 watts from said paper cooler, at least about 300 watts from each of said pre-cooling auxiliary fan and said post-cooling auxiliary fan, at least about 2500 watts from said paper heater, and at least about 4000 watts from said one or more pathways through frame portions included in said first interior volume.

5                    52.     The air quality management apparatus according to Claim 1, wherein said managing of an air quality of air included in and circulating within said second interior volume includes removing excess heat generated within said second interior volume, said removing said excess heat by said air-conditioning device.

10                   53.     The air quality management apparatus according to Claim 52, wherein said heat generated within said second interior volume is generated according to the following heat generation rates: at least about 500 watts from said image writers, at least about 500 watts said modules in addition to said image writers, at least about 2250 watts from said at least one air recirculation device,  
15                   and at least about 1500 watts from heat-generating devices housed in said auxiliary chambers included in said second interior volume, said auxiliary chambers associated with and not included in said modules, said heat-generating devices for operating said recirculation portion, said heat-generating devices including mechanical devices, power supplies, motors, electrical equipment, and  
20                   electrical circuit boards.

                     54.     The air quality management apparatus according to Claim 52, wherein said respective inlet port filter and said entry filter are high throughput filters for filtering airborne particles from said ambient air entering respectively said first interior volume and said fourth interior volume, said high throughput  
25                   filters similar to commercial residential furnace filters.

                     55.     The air quality management apparatus according to Claim 19, said printer further including a fourth interior volume, said air-conditioning device encompassing said fourth interior volume, said fourth interior volume distinct from each of said first interior volume and said second interior volume,

said air conditioning device including a closed-loop circuit for flowing a refrigerant through successive devices included in said closed-loop circuit, said refrigerant being circulated as a refrigerant flow by a refrigerant circulation mechanism, said successive devices through which said refrigerant being  
5 circulated comprising:

said evaporator coil, included in said second interior volume, in which said evaporator coil said refrigerant is evaporated from a liquid state to form a refrigerant gas;

a pressure regulator, located downstream from said evaporator coil, said  
10 pressure regulator included in said second interior volume;

a compressor, located downstream from said evaporator coil, said compressor for compressing said refrigerant gas to a compressed refrigerant gas, said compressor included in said second interior volume;

a gate, located downstream from said compressor, said gate for dividing  
15 said refrigerant flow into a main refrigerant flow and an intermittent auxiliary refrigerant flow, said gate activated by a solenoid valve for intermittently flowing said intermittent auxiliary refrigerant flow through said reheat coil, said gate included in said second interior volume;

a condenser coil, said condenser coil included in said fourth interior  
20 volume, said condenser coil located downstream from said gate and downstream from said reheat coil, to which said condenser coil said main refrigerant flow and said intermittent auxiliary refrigerant flow are together flowed, said condenser coil for cooling and thereby at least partially condensing said compressed refrigerant gas to said liquid state;

25 an expansion valve located downstream from said condenser coil, said expansion valve included in said second interior volume; and

wherein ambient air is drawn as an ambient input airflow from outside said printer through an inlet into said fourth interior volume by an air moving device, said inlet provided with an entry filter, said ambient input airflow directed through  
30 an air compressor for compressing said ambient input airflow, said air compressor included in said fourth interior volume, said ambient input airflow subsequently

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30

flowed past thermally conductive cooling fins, said thermally conductive cooling fins in thermal contact with said condenser coil, such that heat absorbed by said ambient input airflow from said refrigerant within said condenser coil causes said compressed airflow to become a heated airflow, which heated airflow after  
5 flowing past said condenser coil is passed through an exit duct leading from said fourth interior volume to a location for disposal outside of said printer.

56. The air quality management apparatus according to Claim 19, said printer further including

a fourth interior volume, said air-conditioning device encompassing said  
10 fourth interior volume, said fourth interior volume distinct from each of said first interior volume and said second interior volume, said air conditioning device including a closed-loop circuit for flowing a refrigerant through successive devices included in said closed-loop circuit, said refrigerant being circulated as a refrigerant flow by a refrigerant circulation mechanism, said successive devices  
15 through which said refrigerant being circulated comprising:

an evaporator coil, said evaporator coil included in said second interior volume, in which said evaporator coil said refrigerant is evaporated from a liquid state to form a refrigerant gas;

a pressure regulator, located downstream from said evaporator coil, said  
20 pressure regulator included in said second interior volume;

a compressor, located downstream from said evaporator coil, said compressor for compressing said refrigerant gas to a compressed refrigerant gas, said compressor included in said second interior volume;

a gate, located downstream from said compressor, said gate for dividing  
25 said refrigerant flow into a main refrigerant flow and a controlled auxiliary refrigerant flow, said gate activated by a 3-way continuously variable valve for controllably flowing said controlled auxiliary refrigerant flow through said reheat coil, said gate included in said second interior volume;

a condenser coil, said condenser coil included in said fourth interior  
30 volume, said condenser coil located downstream from said gate and downstream from said reheat coil, to which said condenser coil said main refrigerant flow and

said intermittent auxiliary refrigerant flow are together flowed, said condenser coil for cooling and thereby at least partially condensing said compressed refrigerant gas to said liquid state;

an expansion valve located downstream from said condenser coil, said  
5 expansion valve included in said second interior volume; and

wherein ambient air is drawn as an ambient input airflow from outside said printer through an inlet into said fourth interior volume by an air moving device, said inlet provided with an entry filter, said ambient input airflow directed through an air compressor for compressing said ambient input airflow, said air compressor  
10 included in said fourth interior volume, said ambient input airflow subsequently flowed past thermally conductive cooling fins, said thermally conductive cooling fins in thermal contact with said condenser coil, such that heat absorbed by said ambient input airflow from said refrigerant within said condenser coil causes said compressed airflow to become a heated airflow, which heated airflow after  
15 flowing past said condenser coil is passed through an exit duct leading from said fourth interior volume to a location for disposal outside of said printer.

57. The air quality management apparatus according to Claim 55, said air moving device being a blower for blowing said mixture through said exit duct, wherein said blower provides a first suction for drawing said ambient air  
20 into said fourth interior volume, and wherein said blower applies a second suction to said one or more outlet ports from said first interior volume, said second suction for drawing ambient air from outside of said printer through said at least one inlet port into said first interior volume, each said at least one inlet port provided with a respective inlet port filter.

25 58. The air quality management apparatus according to Claim 55 wherein said refrigerant circulation mechanism is operated for sporadically flowing said refrigerant through said evaporator coil at a duty cycle of less than about 10%, and wherein said refrigerant, having passed through said evaporator coil, is diverted by a valve into a shunt pipe and flowed directly to said condenser  
30 coil, said shunt pipe bypassing said pressure regulator as well as said compressor,

said sporadically flowing said refrigerant made to occur when operation of a humidification system for humidifying said air-conditioned air experiences an operational failure, said humidification system for operation in conjunction with said air-conditioning device.

5                    59.     The air quality management apparatus according to Claim 58, wherein said duty cycle is less than about 5%.

60.     The air quality management apparatus according to Claim 54, wherein said ambient inlet air flow into said fourth interior volume is about at least 1250 cubic feet per minute.

10                   61.     The air quality management apparatus according to Claim 54, wherein said refrigerant comprises at least one fluorohydrocarbon.

62.     The air quality management apparatus according to Claim 61, wherein said at least one fluorohydrocarbon is a mixture of about 50 percent by weight difluoromethane and about 50 percent by weight pentafluoroethane.

15                   63.     The air quality management apparatus according to Claim 1, wherein said at least one air recirculation device includes a main blower for blowing said at least one post-exit airflow into and through said plurality of pathways included in said second interior volume.

20                   64.     The air quality management apparatus according to Claim 49, said fusing station including a fuser, wherein a fusing-station-related flow of air included in said air flowing through and included in said first interior volume flow proximate to said fusing station yet not through said fusing station, said fusing-station-related flow carrying fuser oil volatiles emitted by said fuser away from said fuser, wherein said fusing station is sited within said first interior  
25     volume at a location such that substantially none of said fuser oil volatiles reaches said modules via said leakage flow rate of air from said first interior volume to said second interior volume, said fuser oil volatiles being swept away by said fusing-station-related flow for inclusion in said expelled air.

65. A method for managing quality of air within an electrostatographic printer having a paper conditioning station associated therewith, said printer for making color images on receiver members, said air included in a first interior volume and in a second interior volume within said printer, said second interior volume including a plurality of electrostatographic image-forming modules, said first interior volume including paper handling equipment, a fusing station and a post-fusing cooler, said second interior volume differentiated from said first interior volume by at least one separating member, said method for managing air quality comprising the following steps:
- 10 flowing an airflow through said first interior volume, said airflow originating as a filtered intake flow of ambient air flowing from outside said printer into said first interior volume via at least one inlet port, said airflow including an outflow of air flowing at a predetermined rate of flow out of said first interior volume via at least one outlet port to a location outside said printer, said
  - 15 filtered intake flow compensating said outflow, said outflow carrying away through said exit port excess heat and aerial contaminations generated within said first interior volume;  
causing air within said second interior volume to be recirculated through an air-conditioning device for providing a plurality of air-conditioned airflows,
  - 20 said plurality of air-conditioned airflows passing through a plurality of pathways within said second interior volume, a respective air-conditioned airflow included in said plurality of air-conditioned airflows having a respective temperature and a respective relative humidity, said respective temperature and said respective relative humidity measured for said respective air-conditioned airflow leaving said
  - 25 air-conditioning device, said respective air-conditioned airflow for delivery to a respective designated location within said second interior volume, said respective designated location inclusive of: said modules, any components of said modules, and any devices for operating said modules;
  - 30 establishing, for said plurality of recirculating airflows within said second interior volume, a predetermined total rate of recirculation of air for recycling through said air-conditioning device;

providing at least one filtering unit for removing aerial contaminations from said air for recycling by said air-conditioning device; and

providing a determinate leakage path for a pre-specified amount of air leakage between said first interior volume and said second interior volume.

5                    66.     The method for managing air quality according to Claim 65, wherein said pre-specified amount is substantially zero.

67.     The method for managing air quality according to Claim 65, wherein said predetermined rate of flow of air flowing out from said first interior volume is approximately equal to said specified total rate of recirculation of air circulating within said second volume.

10

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193